

ER DkW DBY GENERAT STA



Designed for Easy Installation & Maintenance

- · Easy to move into installation location with two-wheel dolly
- Approved for installation as close as 18" to a building²
- Removable roof and side panels provide better service access to the engine and alternator

Compact Size

- The smallest generator footprint in its class
- Perfect for small properties

Symphony[®] II Power Management System

- Customizable to your home's needs
- Automatically balances the power of your home's electrical load including high wattage items like air conditioning units and electric ovens
- Offers whole house power with a more affordable home generator

BRIGGS & STRATTON® THE SMART CHOICE

For the discerning homeowner that is looking for the smartest, most reliable permanent backup power solution.

FORTRESS[®]

Introducing our dealer exclusive line. Available at your local Briggs & Stratton Dealer with these great features:

- The industry's longest parts, labor and travel limited warranty
- Installed oil warmer for increased starting protection in colder weather



Commercial-Grade Briggs & Stratton Vanguard[™] Engine

- Powerful V-Twin OHV engine
- Easy conversion between natural gas (NG) and liquid propane vapor (LP) during installation

Quality Clean Power

• Ensures your electronics are safely powered

Corrosion Resistant Enclosure & Base

- Made with automotive grade galvanneal steel to resist rust
- Powder-coated paint for years of protection against chips and abrasions



GENERATOR SET RATINGS									
LIQUID PROPANE NATURAL GAS LIMITED WARR								LIMITED WARRANTY ⁴	
MODEL	VOLTAGE	PHASE	HZ	BREAKER	LP kW	LP AMPS	NG kW	NG AMPS	PARTS, LABOR, TRAVEL
Fortress 040545	120/240	1	60	50	10	41.7	9	37.5	6 Year
Briggs & Stratton 040375	120/240	1	60	50	10	41.7	9	37.5	5 Year

¹ This generator is rated in accordance with UL (Underwriters Laboratories) 2200 (stationary engine generator assemblies)

and CSA (Canadian Standards Association) standard C22.2 No. 100-04 (motors and generators)

² The installation manual contains specific instructions related to generator placement in addition to NFPA 37, including the requirement that carbon monoxide detectors be installed and maintained in your home.

³ Warranty details available at www.briggsandstratton.com





ENGINE SPECIFICATIONS						
ENG	INE	LUBRICATION				
Engine Model	Briggs & Stratton Vanguard™	Oil Capacity (oz)	48			
Engine Model Type Trim Number	359775-0003E1	Lubrication System	Full Pressure			
Engine Speed (RPM)	3600	Recommended Oil	5W30 Full Synthetic			
Engine Fuel	Liquid Propane (LP) or Natural Gas (NG)	Low Oil Pressure Sensor	Yes			
Engine Cylinder Configuration	OHV	ALTERNA	TOR SPECS			
Number of Cylinders	2	Manufacturer	Briggs & Stratton			
Displacement (cc)	35 / 570	Туре	Self-Excited, Rotation Field			
Bore & Stroke (in)	2.83 / 2.76	Voltage Regulator	Automatic			
Compression Ratio	8.3:1	Insulation	Class F			
Governor Type	Mechanical	CONTROLL	ER FEATURES			
requency Regulation	+/- 2.5 Hz	Hour Meter	Yes			
		LED Digital Display	Yes			
/alves	OHV with Hardened Seats	Fault Code Display	Yes			
gnition System	Fixed Timing	Weekly Exerciser	Yes			
starter Motor Rating Voltage	12 Volt		100			

Battery

OPERATIONS

FUEL CONSUMPTION ¹							
	50%	Load	100% Load				
Liquid Propane	42.8 ft ³ / hr 1.19 gal / hr		65.6 ft³ / hr	1.82 gal / hr			
Natural Gas	111 ft³ / hr	_	169 ft³ / hr	_			

12 Volt

SOUND RATING AT 7 METERS

67 dBA

Lowest measurement of 12 microphones around generator. Sound level measurement at other locations around generator may be different depending upon installation configuration.

¹ Fuel consumption rates are estimated based on normal operating conditions. Generator operation may be greatly affected by elevation and the cycling operation of multiple electrical appliances – fuel flow rates may vary depending on these factors.


10kW STANDBY GENERATOR




ADDITIONAL INFORMATION							
OTHER	R FEATURES	CERTIFICATION					
Enclosure Material	Galvanneal Steel with Corrosion Resistant Paint	CARB Compliant	Ye	25			
Overcrank Protection	Yes	NFPA Approved	Ye	25			
Engine Warm Up (sec)	20 or 50 Automatic Transfer Switch Controlled	cUL Listed to CSA 22.2 NO 100-	04 Ye	95			
Engine Cool Down (min)	1	NEMA Compliant	Ye	?S			
Response Time (sec)	26 or 56 Automatic Transfer Switch Controlled	EPA Certified Fuel System	Ye	es			
Monitoring Options	Basic Wireless Monitor InfoHub™ Monitor	AVAILABLE ACCESSORIES					
Continuous Battery Charging	Yes	Maintenance Kit 6035					
		Cold Weather Kit	Fortress	6404			
WEIGHT AI	ND DIMENSIONS		Briggs & Stratton	6030A			
Assembled Weight (lbs)	272	Basic Wireless Monitor	6264				
Overall Dimensions (in)	28 x 24.4 x 35.1	InfoHub	62	60			
Packaged Weight (lbs)	330	Remote Status Monitor	61	44			

Packaged Dimensions (in)

39 x 35.5 x 42







FUEL PIPE SIZE RECOMMENDATION CHART (CAPACITY IN THOUSANDS OF BTU/HOUR)

Natural Gas. / Inlat Pressure lass than 2 BSI / Pressure Drep 1/2" Water Column. / Specific Gravity 0.60

	1/2" pipe capacity	3/4" pipe capacity	1" pipe capacity	1-1/4" pipe capacity	1-1/2" pipe capacity	2" pipe capacity	
20' Length [*]	118	247	466	957	1,430	2,760	
40' Length*	81	170	320	657	985	1,900	
60' Length*	65	137	257	528	791	1,520	
80' Length*	56	117	220	452	677	1,300	
100' Length*	50	104	195	400	600	1,160	

Liquid Propane / Inlet Pressure 11" Water Column / Pressure Drop 1/2" Water Column / Specific Gravity 1.50

	1/2" pipe capacity	3/4" pipe capacity	1" pipe capacity	1-1/4" pipe capacity	1-1/2" pipe capacity	2" pipe capacity
20' Length [*]	200	418	788	1,617	2,423	4,666
40' Length*	137	287	541	1,111	1,665	3,207
60' Length*	110	231	435	892	1,337	2,575
80' Length*	101	212	400	821	1,230	2,370
100' Length*	101	212	400	821	1,230	2,370

*Total length of piping from outlet of regulator to appliance furthest away.

ADDITIONAL INFORMATION

TRANSFER SWITCH SPECIFICATIONS					
Prewired 16 Circuit	100 AMP	Model #071076			
Standard 16 Circuit	100 AMP	Model # 071047			
Symphony [®] II	100 AMP	Model # 071071			
Symphony [®] II	150 AMP	Model # 071070			
Symphony [®] II	200 AMP	Model # 071068			
Voltage Rating	120/240				
	Select Circuit: 16				
Number of Protected Circuits	Symphony [®] II: Whole House				
UL Approved		Yes			
NEMA 3R Rated	Yes				



25 Mohawk Drive, Suite D Leominster, MA 01453 www.electricsynergy.com generators@electricsynergy.com

CALL TODAY FOR A FREE IN-HOME ESTIMATE! 978.537.9473

Disclaimer: Not for Prime Power or use where standby systems are legally required, for serious life safety or health hazards, or where lack of power hampers rescue of fire-fighting operations.